


Mocowanie

Na haku typu BQC 12 50, uchwycie typu CSC 12 lub CSC 8 (nie dołączone).

Materiał

Stal ocynkowana ogniowo

Stal ocynkowana zgodnie z normą ASTM 498 Klasa A lub stal powlekana aluminium.

KOD	OPIS	Średnica kabla Ø (mm)	Kolor	Opakowanie	 (kg)
P150920809	SS FO C 88-93	8.8-9.29		10	0,660
P150920910	SS FO C 93-99	9.3-9.89		10	0,660
P150921010	SS FO C 99-105	9.9-10.49		10	0,750
P150921011	SS FO C 105-111	10.5-11.09		10	0,675
P150921112	SS FO C 111-118	11.1-11.79		10	0,790
P150921180	SS FO C 118-125	11.8-12.49		10	0,840
P150921213	SS FO C 125-133	12.5-13.29		10	0,850
P150921314	SS FO C 133-141	13.3-14.09		10	0,880
P150921415	SS FO C 141-149	14.1-14.89		10	0,890
P150921516	SS FO C 149-159	14.9-15.89		10	0,970
P150921617	SS FO C 159-168	15.9-16.79		10	0,970
P150921819	SS FO C 168-178	16.8-17.79		10	0,975
P150921718	SS FO C 178-187	17.8-18.69		10	1,070
P150921920	SS FO C 187-199	18.7-19.89		10	1,150
P150921921	SS FO C 199-211	19.9-21.09		10	1,200
P150922122	SS FO C 211-224	21.1-22.39		10	1,120
P150922240	SS FO C 224-237	22.4-23.69		10	1,170
P150922425	SS FO C 237-249	23.7-24.89		10	1,275
P150922526	SS FO C 249-261	24.9-26.09		10	1,355

Podane charakterystyki mają charakter informacyjny i mogą ulec zmianie bez wcześniejszego powiadomienia. Zdjęcia mają charakter poglądowy.

FPP150921XXX_SSFOC_202310_FGB

